

型号 Type	参数 Parameter	级数 Stage	流量Q Capacity		扬程 Head H m	转速 Speed n r/min	效率 Eff. %	轴功率 Shaft power kW	配带电动机 Motor		必需汽 蚀余量 NPSHr m	叶轮名 义直径 Impeller Dia mm	泵重 Weight kg	电机重 Motor Weight kg
			m³/h	L/s					功率 Power kW	型号 Type				
D(MD, DF) 6-25×(2~12)		2	3.75 8.75	1.04 1.75 2.08	50 49	2950	37.4 46.5 49	1.49 1.84 2.08	3	Y100L-2	2.0 2.0 2.5	φ139.5	77.2	33
		3	3.75 7.5	1.04 1.75 2.08	76.5 75 73.5	2950	36 48	2.23 2.77 3.12	5.5	Y132S1-2	2.0 2.0 2.5	φ139.5	85.5	64
		4	3.75 7.5	1.04 1.75 2.08	102 100 98	2950	35.6 48	2.98 3.69 4.16	7.5	Y132S2-2	2.0 2.0 2.5	φ139.5	94.4	70
		5	3.75 7.5	1.04 1.75 2.08	127.5 125.5 122.5	2950	35.6 48	3.73 4.61 5.20	7.5	Y132S2-2	2.0 2.0 2.5	φ139.5	102.9	70
		6	3.75 7.5	1.04 1.75 2.08	153 150 147	2950	35 46.5	4.47 5.53 6.24	11	Y160M1-2	2.0 2.0 2.5	φ139.5	111.5	117
		7	3.75 7.5	1.04 1.75 2.08	178.5 175 171.5	2950	35 46.5	5.22 6.45 7.28	11	Y160M1-2	2.0 2.0 2.5	φ139.5	120.0	117
		8	3.75 7.5	1.04 1.75 2.08	200 196 191.5	2950	35 46.5	5.96 7.37 8.32	15	Y160M2-2	2.0 2.0 2.5	φ139.5	128.6	125
		9	3.75 7.5	1.04 1.75 2.08	229.5 225 220.5	2950	35 46.5	6.71 8.29 9.36	15	Y160M2-2	2.0 2.0 2.5	φ139.5	137.1	125
		10	3.75 7.5	1.04 1.75 2.08	259.5 255 250.5	2950	35 46.5	7.46 9.04 10.12	15	Y160M2-2	2.0 2.0 2.5	φ139.5	145.6	125
D(MD, DF) 12-50×(2~12)		10	7.5 15	2.08 3.5	310 310 310	2950	41.6 50	147.2 177.2	22	Y180L-2	2.0 2.0 2.5	φ160	147.2	147
		11	7.5 15	2.08 3.5	340 340 340	2950	41.6 50	165.2 197.2	22	Y180L-2	2.0 2.0 2.5	φ160	165.2	147
		12	7.5 15	2.08 3.5	370 370 370	2950	41.6 50	183.2 215.2	22	Y180L-2	2.0 2.0 2.5	φ160	183.2	147
		2	7.5 15	2.08 3.5	400 400 400	2950	41.6 50	201.2 233.2	22	Y180L-2	2.0 2.0 2.5	φ160	201.2	147
		4	7.5 15	2.08 3.5	430 430 430	2950	41.6 50	219.2 251.2	22	Y180L-2	2.0 2.0 2.5	φ160	219.2	147
		5	7.5 15	2.08 3.5	460 460 460	2950	41.6 50	237.2 269.2	22	Y180L-2	2.0 2.0 2.5	φ160	237.2	147
		6	7.5 15	2.08 3.5	490 490 490	2950	41.6 50	255.2 287.2	22	Y180L-2	2.0 2.0 2.5	φ160	255.2	147
		7	7.5 15	2.08 3.5	520 520 520	2950	41.6 50	273.2 305.2	22	Y180L-2	2.0 2.0 2.5	φ160	273.2	147
		8	7.5 15	2.08 3.5	550 550 550	2950	41.6 50	291.2 323.2	22	Y180L-2	2.0 2.0 2.5	φ160	291.2	147
		9	7.5 15	2.08 3.5	580 580 580	2950	41.6 50	309.2 341.2	22	Y180L-2	2.0 2.0 2.5	φ160	309.2	147
		10	7.5 15	2.08 3.5	610 610 610	2950	41.6 50	327.2 359.2	22	Y180L-2	2.0 2.0 2.5	φ160	327.2	147
		11	7.5 15	2.08 3.5	640 640 640	2950	41.6 50	345.2 377.2	22	Y180L-2	2.0 2.0 2.5	φ160	345.2	147
D(MD, DF) 15-50×(2~12)		10	11.25 22.5	3.12 5.3	370 370 370	2950	47.9 56	165.2 197.2	22	Y200L-2	2.0 2.0 2.5	φ160	165.2	147
		11	11.25 22.5	3.12 5.3	400 400 400	2950	47.9 56	183.2 215.2	22	Y200L-2	2.0 2.0 2.5	φ160	183.2	147
		12	11.25 22.5	3.12 5.3	430 430 430	2950	47.9 56	201.2 233.2	22	Y200L-2	2.0 2.0 2.5	φ160	201.2	147
		2	11.25 22.5	3.12 5.3	460 460 460	2950	47.9 56	219.2 251.2	22	Y200L-2	2.0 2.0 2.5	φ160	219.2	147
		4	11.25 22.5	3.12 5.3	490 490 490	2950	47.9 56	237.2 269.2	22	Y200L-2	2.0 2.0 2.5	φ160	237.2	147
		5	11.25 22.5	3.12 5.3	520 520 520	2950	47.9 56	255.2 287.2	22	Y200L-2	2.0 2.0 2.5	φ160	255.2	147
		6	11.25 22.5	3.12 5.3	550 550 550	2950	47.9 56	273.2 305.2	22	Y200L-2	2.0 2.0 2.5	φ160	273.2	147
		7	11.25 22.5	3.12 5.3	580 580 580	2950	47.9 56	291.2 323.2	22	Y200L-2	2.0 2.0 2.5	φ160	291.2	147
		8	11.25 22.5	3.12 5.3	610 610 610	2950	47.9 56	309.2 341.2	22	Y200L-2	2.0 2.0 2.5	φ160	309.2	147
		9	11.25 22.5	3.12 5.3	640 640 640	2950	47.9 56	327.2 359.2	22	Y200L-2	2.0 2.0 2.5	φ160	327.2	147
		10	11.25 22.5	3.12 5.3	670 670 670	2950	47.9 56	345.2 377.2	22	Y200L-2	2.0 2.0 2.5	φ160	345.2	147
		11	11.25 22.5	3.12 5.3	700 700 700	2950	47.9 56	363.2 395.2	22	Y200L-2	2.0 2.0 2.5	φ160	363.2	147
D(MD, DF) 18-50×(2~12)		10	15 30	4.17 7.13	430 430 430	2950	54.5 63	197.2 229.2	22	Y220L-2	2.0 2.0 2.5	φ160	197.2	147
		11	15 30	4.17 7.13	460 460 460	2950	54.5 63	215.2 247.2	22	Y220L-2	2.0 2.0 2.5	φ160	215.2	147
		12	15 30	4.17 7.13	490 490 490	2950	54.5 63	233.2 265.2	22	Y220L-2	2.0 2.0 2.5	φ160	233.2	147
		2	15 30	4.17 7.13	520 520 520	2950	54.5 63	251.2 283.2	22	Y220L-2	2.0 2.0 2.5	φ160	251.2	147
		4	15 30	4.17 7.13	550 550 550	2950	54.5 63	269.2 301.2	22	Y220L-2	2.0 2.0 2.5	φ160	269.2	147
		5	15 30	4.17 7.13	580 580 580	2950	54.5 63	287.2 319.2	22	Y220L-2	2.0 2.0 2.5	φ160	287.2	147
		6	15 30	4.17 7.13	610 610 610	2950	54.5 63	305.2 337.2	22	Y220L-2	2.0 2.0 2.5	φ160	305.2	147
		7	15 30	4.17 7.13	640 640 640	2950	54.5 63	323.2 355.2	22	Y220L-2	2.0 2.0 2.5	φ160	323.2	147
		8	15 30	4.17 7.13	670 670 670	2950	54.5 63	341.2 373.2	22	Y220L-2	2.0 2.0 2.5	φ160	341.2	147
		9	15 30	4.17 7.13	700 700 700	2950	54.5 63	359.2 391.2	22	Y220L-2	2.0 2.0 2.5	φ160	359.2	147
		10	15 30	4.17 7.13	730 730 730	2950	54.5 63	377.2 409.2	22	Y220L-2	2.0 2.0 2.5	φ160	377.2	147
		11	15 30	4.17 7.13	760 760 760	2950	54.5 63	395.2 427.2	22	Y220L-2	2.0 2.0 2.5	φ160	395.2	147
D(MD, DF) 21-50×(2~12)		10	18.75 37.5	5.0 8.5	490 490 490	2950	61.8 70	229.2 261.2						